

## Rodamiento de agujas TRU456430-UU-IKO - TRU456430-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/tru456430-uu-iko>

**IKO**  
**ROLLER BEARINGS**

Caged Roller Bearings [With Seal]  
Full Complement Roller Bearings [With Seal]

Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r <sup>(1)</sup> min	J
45	---	---	TRU 456430UU	295	45	64	30	0.6	50.5
$E_w$	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed n <sub>2</sub> r/min						
61	36 400	54 700	2 500						

Notes: (1) Minimum allowable value of chamfer dimension r.  
(\*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952386171
Diámetro interior	45 mm
Diámetro exterior	64 mm
Espesor	30 mm
Peso	300 g
Envasado	-
Estándar	-

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE