








Rodamiento de agujas NAU4919-UU-IKO - NAU4919-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/nau4919-uu-iko>



ROLLER BEARINGS

Caged Roller Bearings  
Full Complement Roller Bearings  

NAU49-UU
TRU-UU

| Shaft dis. mm | Identification number | | Mass (Ref.) g | Boundary dimensions mm | | | | |
|----------------------|-----------------------------|---|---|------------------------|-----|----|-----------------------------------|-----|
| | Full complement type | Caged type | | d | D | C | r _{1 min} ⁽¹⁾ | J |
| 95 | --- | NAU 4919UU | 1 270 | 95 | 130 | 35 | 1.5 | 106 |
| <i>E_w</i> | Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed n ₂ rpm | | | | | |
| 120.5 | N 81 000 | N 136 000 | 1 800 | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and TRU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952386560 |
| Diámetro interior | 95 mm |
| Diámetro exterior | 130 mm |
| Espesor | 35 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE