


Rodamiento de agujas NAG4920-UU-IKO - NAG4920-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/nag4920-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings [With Seal]
Full Complement Roller Bearings [With Seal]



NAG49--UU

Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r ⁽¹⁾	J
100	NAG 4920UU	—	1 850	100	140	40	1.5	114.5
E_w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n ₂ rpm					
129.5	N	N	1,200					

Notes^(*)
⁽¹⁾ Minimum allowable value of chamfer dimension r
^(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952386577
Diámetro interior	100 mm
Diámetro exterior	140 mm
Espesor	40 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE