




Rodamiento de agujas NAU4926-UU-IKO - NAU4926-UU-IKO


<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/nau4926-uu-iko>



ROLLER BEARINGS

Caged Roller Bearings  **With Seal**

Full Complement Roller Bearings  **With Seal**



NAU49—UU
TRU—UU

Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r _{fs} (1)	J
130	—	NAU 4926UU	3 610	130	180	50	2	147
<i>E_w</i>	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed (1) rpm					
165.5	N	N	1,300					

Notes(1) Minimum allowable value of chamfer dimension r
 (2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAU and TRU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952386690
Diámetro interior	130 mm
Diámetro exterior	180 mm
Espesor	50 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE