


Rodamiento de agujas NAS5011-ZZ-NR-IKO - NAS5011-ZZ-NR-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/nas5011-zz-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
55		NAS 5011ZZNR	1.15	55	90	94.8	46	45	34	5.5
<i>f</i>	<i>c</i>	<i>r</i> mm ⁽¹⁾	<i>J</i>	Basic dynamic load rating C N		Static load rating C ₀ N		Allowable rotational speed ⁽²⁾ rpm		
2.5	2	0.6	68	118 000		193 000		1 800		

Notes⁽¹⁾ Minimum allowable value of chamfer dimension *r*
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAG and NAU series with a bore diameter, *d*, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952386799
Diámetro interior	55 mm
Diámetro exterior	90 mm
Espesor	46 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE