


Rodamiento de agujas NAX6040Z-IKO - NAX6040Z-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/nax6040z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS
Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring



Identification number														
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		Mass (Ref.) g					
	NAX 6040Z		454		---		---							
Boundary dimensions mm														
F_w	D	D_1	D_2	L	H	r_1 min.	d_f	Basic rolling stress d_a Min. mm	Basic dynamic load rating C Radial Axial	Basic static load rating C_0 Radial Axial	Allowable rotational speed ⁽²⁾ rpm			
60	72	85	86.5	40	17	12	1	60	75	47 500	41 400	103 000	89 700	4 000

Notes:
(1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952390376
Diámetro interior	60 mm
Diámetro exterior	72 mm
Espesor	40 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE