


Rodamiento de agujas NBX6040Z-IKO - NBX6040Z-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/nbx6040z-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring



Shaft dia. mm	Mass (Ref.) g		With dust cover Mass (Ref.) g		Mass (Ref.) g		With dust cover Mass (Ref.) g		Identification number
60	---	---	---	---	---	---	---	---	NBX 6040Z

F _w	D	D ₁	D ₂	L	H	f _s min.	d _i	Basic load rating C	Basic dynamic load rating C ₁₀		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	
									Radial	Axial	Radial	Axial		
60	72	85	86.5	40	17	12	1	60	82	47 500	64 600	103 000	224 000	4 000

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.

Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3663952390529
Diámetro interior	60 mm
Diámetro exterior	72 mm
Espesor	40 mm
Envasado	1
Estándar	Ninguna norma

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE