

## Rodamiento de agujas NAXI923-IKO - NAXI923-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/naxi923-iko>

**LINEAR TYPE NEEDLE ROLLER BEARINGS**

Needle Bearings with Thrust Ball Bearing With Inner Ring  
Needle Bearings with Thrust Roller Bearing With Inner Ring

Identification number														
		Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			<i>d</i>				
<b>NAXI</b>	<b>923</b>	49.5	—	—	—	—	—			9				
Boundary dimensions mm		Bore diameter mm		Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup>	Assemble					
<i>B</i>	<i>H</i>	<i>I</i> <sub>1</sub>	<i>r</i> <sub>max</sub>	<i>r</i> <sub>min</sub>	Radial	Radial	Radial	Radial	rpm					
16	9	6.5	0.3	0.3	12	12	20	11	9 250	9 670	11 200	11 100	9 000	LRT

Minimum allowable value of chamfer dimension *r*  
Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in IAX series, and a maximum of 25% of this value is allowable in the NBSX series.  
The outer ring has an oil groove and an oil hole.  
Grease is not prepacked. Perform proper lubrication.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952390666
Diámetro interior	9 mm
Diámetro exterior	21 mm
Espesor	23 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE