


Rodamiento de agujas NAXI2530-IKO - NAXI2530-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/naxi2530-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**



| Shaft dia. mm | Identification number | | | | | | d | D | D _i |
|------------------|-----------------------|-----------------|------------------|-----------------|------------------|-----------------|----|----|----------------|
| | Mass (Ref.) g | With dust cover | Mass (Ref.) g | With dust cover | Mass (Ref.) g | With dust cover | | | |
| 25 | NAXI 2530 | 179 | — | — | — | — | 25 | 42 | 47 |

| Boundary dimensions mm | | | | Bore diameter mm | Basic dynamic load rating C | Basic static load rating C ₀ | | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | | | | | | | | | | |
|---------------------------|----|------|----|---------------------|--------------------------------|--|-------|--|----------------------|--------|-------|-----|----|-----|----|-----|---|-----|------------|
| D ₂ | L | B | H | | | Radial | Axial | | | Radial | Axial | | | | | | | | |
| 48 | 30 | 20.5 | 11 | 9.5 | 0.6 | 0.3 | 30 | 40 | 25 | 100 | 20 | 400 | 40 | 100 | 33 | 600 | 6 | 500 | LRT 253020 |

Notes:
 (1) Minimum allowable value of chamfer dimension r.
 (2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
 Remark 1: The outer ring has an oil groove and an oil hole.
 2: Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952390840 |
| Diámetro interior | 25 mm |
| Diámetro exterior | 42 mm |
| Espesor | 30 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE