


Rodamiento de agujas NAXI4032-IKO - NAXI4032-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/naxi4032-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**



Shaft dia. mm	Identification number						d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
40	NAXI 4032	315	—	—	—	—	40	58	65

Boundary dimensions mm				Bore diameter mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRT 404520
D ₂	L	B	H			Radial	Radial		
66.5	32	20	14	9	31 000	27 900	60 200	55 100	5 000

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
 Remarks: 1. The outer ring has an oil groove and an oil hole.
 2. Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952390963
Diámetro interior	40 mm
Diámetro exterior	58 mm
Espesor	32 mm
Envasado	-

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE