


Rodamiento de agujas NBXI4032Z-IKO - NBXI4032Z-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/nbxi4032z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring
Needle Roller Bearings with Thrust Roller Bearing With Inner Ring



Shaft dia. mm	Identification number										d	D	D ₁	
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	NBXI 4032Z							353
40	---	---	---	---	---	---	NBXI 4032Z				353	40	58	65

Boundary dimensions mm			r ⁽¹⁾	r _{max}	r _{min}	d ₄	d ₅	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRT 404520		
D ₂	L	B						Radial	Axial	Radial	Axial				
66.5	32	20	14	9	0.6	0.3	45	62	44	31 000	40 800	60 200	133 000	5 500	LRT 404520

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: Z: The outer ring has an oil groove and an oil hole.
1: Grease is not prepacked. Perform proper lubrication.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952390994
Diámetro interior	40 mm
Diámetro exterior	58 mm
Espesor	32 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE