

## Rotulas GE SB75A-IKO - SB75A-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/sb75a-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree
			$d$	$D$	$B$	$C$	$d_k$	$r_1$ mm <sup>(1)</sup>	
75	<b>SB 75A</b>	3.02	75	120	64	55	110	0.6	5
Mounting dimensions mm		Dynamic load capacity $C_d$ N	Static load capacity $C_s$ N						
$d_s$ Min.	Max. <sup>(2)</sup>		$D_s$ Min.	Max.					
79.5	89.5	593 000	115.5	102					

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952391427
Diámetro interior	75 mm
Diámetro exterior	120 mm
Espesor	64 mm
Tipo	GE
Lubricación	sin
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE