


Rotulas GE SB80A-IKO - SB80A-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/sb80a-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree α
	SB	SA		d	D	B	C	d_k	r_1 mm ⁽¹⁾	
80	SB	80A	3.98	80	130	70	60	120	0.6	5
Mounting dimensions mm		Dynamic load capacity C_d N		Static load capacity C_s N						
d_s	Max. ⁽²⁾	Min.	Max.	Min.	Max.					
84.5	97.5	125.5	112	706 000	4 240 000					

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952391441
Diámetro interior	80 mm
Diámetro exterior	130 mm
Espesor	70 mm
Tipo	GE
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE