


Rotulas GE SB90A-IKO - SB90A-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/sb90a-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree
			d	D	B	C	d _k	r ₁ mm ⁽¹⁾	
90	SB 90A	4.71	90	140	76	65	130	0.6	5
Mounting dimensions mm		Dynamic load capacity C _d N	Static load capacity C _s N						
d _s	D _s		C _d	C _s					
Min.	Max. ⁽²⁾	Min.	Max.						
94.5	105.5	135.5	121	829 000	4 970 000				

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952391489
Diámetro interior	90 mm
Diámetro interior	3.543" inch
Diámetro exterior	140 mm
Diámetro exterior	5.512" inch
Espesor	76 mm
Espesor	2.992" inch
Tipo	GE
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE