


Rotulas GE SB95A-IKO - SB95A-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/sb95a-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



| Shaft dia. mm | Identification number | Mass (Ref.) kg | Boundary dimensions mm | | | | | | Permissible tilting angle degree |
|---------------------------|-----------------------|-------------------|---|-----------|--|----|----------------|--------------------|-------------------------------------|
| | | | d | D | B | C | d _k | r _s (1) | |
| 95 | SB 95A | 6.05 | 95 | 150 | 82 | 70 | 140 | 0.6 | 5 |
| Mounting dimensions mm | | | Dynamic load capacity C _d | | Static load capacity C _s | | | | |
| d _s | D _s | | N | N | N | N | | | |
| Min. Max.(2) | Max. Min. | | | | | | | | |
| 99.5 113.5 | 145.5 130 | | 961 000 | 5 770 000 | | | | | |

Notes (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952391502 |
| Diámetro interior | 95 mm |
| Diámetro exterior | 150 mm |
| Espesor | 82 mm |
| Tipo | GE |
| Lubricación | sin |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE