


## Rotulas GE SB11518098-IKO - SB11518098-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/sb11518098-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree $\alpha$
	$d$	$D$		$B$	$C$	$d_k$	$r_1$	$r_2$		
115	<b>SB 11518098</b>		10.3	115	180	98	85	165	1	5
Mounting dimensions mm		Dynamic load capacity $C_d$		Static load capacity $C_s$						
$d_s$	$D_s$									
Min.	Max. <sup>(2)</sup>	Min.	N	N	N					
120.5	132.5	174.5	152	1 380 000	8 250 000					

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952391571
Diámetro interior	115 mm
Diámetro exterior	180 mm
Espesor	98 mm
Tipo	GE
Lubricación	sin
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE