


Rotulas GE SB150220120-IKO - SB150220120-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/sb150220120-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree	
	d	D		B	C	d_k	r_1	r_2		
150	SB 150220120		17.0	150	220	120	105	205	1	5
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s						
d_a	D_a	d_s	D_s	N	N					
Min. 155.5	Max. 166	Min. 214.5	Max. 189	2 110 000	12 700 000					

Notes: (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_a .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952391632
Diámetro interior	150 mm
Diámetro exterior	220 mm
Espesor	120 mm
Tipo	GE
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE