

Rotulas GE GE200ES-2RS-IKO - GE200ES-2RS-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/ge200es-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d_s	r_1 (°)	r_2 (°)	α	α_1
200		GE 200ES-2RS	26.1	200	290	130	100	250	1.1	1.1	7	6
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s								
d_s		D_s		N		N						
Min.	Max.(?)	Min.	Max.	Min.	Max.	Min.	Max.					
207	213.5	283	244	2 450 000	14 700 000							

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952392066
Diámetro interior	200 mm
Diámetro exterior	290 mm
Espesor	130 mm
Tipo	GE
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE