


Rotulas GE GE280ES-IKO - GE280ES-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/ge280es-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d _s	r ₁ (1)	r ₂ (1)	α	α ₁
280	GE 280ES		66.0	280	400	155	120	350	1.1	1.1	6	5
Mounting dimensions mm			Dynamic load capacity C _d N	Static load capacity C _s N								
d _s	D _s											
Min.	Max.(2)	Max.	Min.									
287	313.5	393	345	4 120 000	24 700 000							

Notes (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952392158
Diámetro interior	280 mm
Diámetro exterior	400 mm
Espesor	155 mm
Tipo	GE
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE