


Rotulas GE GE260GS-2RS-IKO - GE260GS-2RS-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/ge260gs-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
260		GE 260GS-2RS	81.8	260	400	205	120	350	1.1	1.1	15	14
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s								
d_s	D_s											
Min. Max.(2)	Max. Min.	N		N								
267 283.5	393 345	4 120 000		24 700 000								

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952392684
Diámetro interior	260 mm
Diámetro interior	10.236" inch
Diámetro exterior	400 mm
Diámetro exterior	15.748" inch
Espesor	205 mm
Espesor	8.071" inch
Tipo	GE
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE