

## Rotulas GE SBB56-IKO - SBB56-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/sbb56-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings Inch Series



Shaft dia. mm (inch)	Identification number		Mass (flat) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
<b>88.900</b> (3 1/2)	<b>SBB 56</b>		<b>4.83</b>	<b>88.900 (3 1/2)</b>	<b>139.700 (5 1/2)</b>	<b>77.77 (3.062)</b>	<b>66.68 (2.625)</b>
Radial internal clearance mm	Mounting dimensions mm		Dynamic load capacity C <sub>d</sub> N	Static load capacity C <sub>s</sub> N			
	d <sub>k</sub>	d <sub>1</sub> r <sub>1</sub> max. r <sub>2</sub> max.		r <sub>1</sub> r <sub>2</sub> max. r <sub>2</sub> max.			
128(5.039)	0.13 / 0.23	101.6	0.6	0.8	837 000	5 020 000	

Notes: (1) Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>k</sub>.  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952392967
Diámetro interior	88.9 mm
Diámetro interior	3 1/2" inch
Diámetro exterior	139.7 mm
Diámetro exterior	5 1/2" inch
Espesor	77.77 mm
Espesor	3.062" inch
Tipo	GE
Lubricación	sin
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE