


Rotulas GE SBB60-2RS-IKO - SBB60-2RS-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/sbb60-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
95.250 (3 7/8)		SBB 60-2RS	6.67	95.250 (3 7/8)	149.225 (5 7/8)	83.34 (3.281)	71.42 (2.812)
d _k	Radial internal clearance mm Min./Max.	Mounting dimensions mm d ₁ r ₁ max. r ₂ max.		Dynamic load capacity C _d N	Static load capacity C _s N		
137 (5.394)	0.13 / 0.23	108.4	0.6 0.8	960 000	5 760 000		

Notes: (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952392998
Diámetro interior	95.25 mm
Diámetro exterior	149.225 mm
Espesor	83.34 mm
Tipo	GE
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE