


Leva de rodamiento CRY32-V-IKO - CRY32-V-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/leva/cry32-v-iko>

IKO
ROLLER FOLLOWERS
Non-separable Roller Followers, Inch Series **Full Complement Type /With Inner Ring**



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions: mm(inch) | | | |
|----------------------------|---------------------------------------|---------------------------------------|---------------------|-------------------------------|--------------------------------|----------------|--------------------------------------------|
| | Shield type Cylindrical outer ring | Sealed type Cylindrical outer ring | | d | D | B | C |
| 15.875 (5/8) | CRY 32 V | | 476 | 15.875 (5/8) | 50.800 (2) | 33.338(1.3125) | 31.750 (1 1/4) |
| | | Shaft dia. | | | Basic dynamic load rating C | | Basic static load rating C ₀ |
| | | Push fit | | Drive fit | | Press fit | |
| | | Min. | Max. | Min. | Max. | Min. | Max. |
| 38.0(1.417) | 1.588 (5/8) | 15.857 | 15.867 | 15.873 | 15.883 | 15.883 | 15.893 |
| | | | | | | 45 700 | 80 600 |

Remarks: 1. The inner ring has an oil hole.
2. Provided with prepacked grease.

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| Nº Ean13 | 3663952398198 |
| Diámetro interior | 15.875 mm |
| Diámetro exterior | 50.8 mm |
| Espesor | 33.338 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE