


## Rodamiento de agujas NA4822-IKO - NA4822-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/na4822-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Inner Ring



Shaft dia. mm	Identification number						Mass (Ref.)				
	NA 49	NA 69	NA 48	TAFI	TRI	GTRI	g	d			
110	—	—	<b>NA 4822</b>	—	—	—	1 200	110			
Boundary dimensions mm			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring		
D	C	B	r <sub>s</sub> min <sup>(2)</sup>	F <sub>w</sub> S <sup>(2)</sup>	Min. d <sub>s</sub>	Max. D <sub>s</sub>	N	N	rpm		
140	30	—	1	120 1	115	118	135	93 200	239 000	3 500	LRT 11012030

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952062952
Diámetro interior	110 mm
Diámetro exterior	140 mm
Espesor	30 mm
Peso	1080 g
Envasado	-
Estándar	-

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE