


## Seguidor de leva CF10-1-VUUM-IKO - CF10-1-VUUM-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cf10-1-vuum-iko>



### CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



| Stud dia.<br>mm        | Identification number   |                  |                             |                |                         |                |                             |                | Mass (Ref.)                    |                                       |                                |  |   |                               |
|------------------------|-------------------------|------------------|-----------------------------|----------------|-------------------------|----------------|-----------------------------|----------------|--------------------------------|---------------------------------------|--------------------------------|--|---|-------------------------------|
|                        | Shield type             |                  |                             |                | Sealed type             |                |                             |                | g                              | D                                     | C                              | d <sub>1</sub>                             |   |                               |
|                        | With crowned outer ring |                  | With cylindrical outer ring |                | With crowned outer ring |                | With cylindrical outer ring |                |                                |                                       |                                |  |   |                               |
| 10                     |                         |                  |                             |                |                         |                | CF 10-1 VUUM                |                | 61                             | 26                                    | 12                             | 10   |   |                               |
| Boundary dimensions mm |                         |                  |                             |                |                         |                |                             |                |                                |                                       |                                |  |   |                               |
| G                      | G <sub>1</sub>          | B <sub>max</sub> | B <sub>1 max</sub>          | B <sub>2</sub> | B <sub>3</sub>          | C <sub>1</sub> | g <sub>1</sub>              | g <sub>2</sub> | f <sup>(1)</sup><br>Min.<br>mm | Mounting diameter<br>f <sub>min</sub> | Maximum tightening torque<br>C | Ball dynamic load rating<br>C <sub>0</sub> | Ball static load rating<br>C <sub>0</sub> | Maximum allowable static load |
| M10 X 1                | 12                      | 13.2             | 36.2                        | 23             | —                       | 0.6            | *4                          | —              | 0.3                            | 16                                    | 14.7                           | 9 570                                      | 14 500                                    | 8 650                         |

## CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | IKO           |
| Nº Ean13          | 3663952440385 |
| Diámetro interior | 10 mm         |
| Diámetro exterior | 26 mm         |
| Espesor           | 12 mm         |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE