


Seguidor de leva CF6-UU-IKO - CF6-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cf6-uu-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UU

Stud dia. mm	Identification number				Mass (Ref.)				
	Shield type		Sealed type		g	D	C	d ₁	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
6					18.5	16	11	6	M 6X1

Boundary dimensions mm													
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max (°)	f Min. mm	Maximum ignoring stress N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N
8	12.2max	28.2max	16	—	0.6	*4	—	0.3	11	2.7	3 660	3 650	1 950

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952440989
Diámetro interior	6 mm
Diámetro exterior	16 mm
Espesor	11 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE