


Seguidor de leva CF8-UUM-IKO - CF8-UUM-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cf8-uum-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UU

Stud dia. mm	Identification number				Mass (Ref.)								
	Shield type		Sealed type		g	D	C	d ₁	G				
B	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	28.5	19	11	8	M 8x1				
CF 8 UUM													
Boundary dimensions mm													
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max (°)	f Min. mm	Maximum ignoring stress N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N
10	12.2max	32.2max	20	—	0.6	*4	—	0.3	13	7.1	4 250	4 740	4 620

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952441061
Diámetro interior	8 mm
Diámetro exterior	19 mm
Espesor	11 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE