


Seguidor de leva CF30-R-IKO - CF30-R-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cf30-r-iko>



CAM FOLLOWERS

Standard Type Cam Follower With Cage/With Screwdriver Slot



Stud dia. mm	Identification number				Mass (Ref.)				
	Shield type		Sealed type		g	D	C	d ₁	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
30	CF 30	R			1 870	80	35	30	M30×1.5

Boundary dimensions mm										Mounting diameter f Min. mm	Maximum tightening torque N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N	
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _{max}	(°)						
32	37	max	100	max	63	15	1	8	4	1	49	438	45 400	85 100	85 100

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952441566
Diámetro interior	30 mm
Diámetro exterior	80 mm
Espesor	35 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE