

Seguidor de leva CFES12-UU-IKO - CFES12-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfes12-uu-iko>

IKO
CAM FOLLOWERS
Solid Eccentric Stud Type Cam Followers With Cage/With Screwdriver Slot

Stud dia. mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d ₁
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
12				CFES 12 UU	95	30	14	12

Boundary dimensions mm										Eccentricity E	Mounting dimension f Min. mm	Maximum tightening torque N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N
G	G ₁	B max	B ₁ max	B ₂	B ₃	C ₁	B ₁	B ₂	z						
M12×1.5	13	15.2	40.2	25	6	0.6	6	3	0.6	0.4	21	21.9	7 910	9 790	9 790

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060459220
Diámetro interior	12 mm
Diámetro exterior	30 mm
Espesor	14 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE