


## Seguidor de leva CFE12-1-B-IKO - CFE12-1-B-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe12-1-b-iko>

**IKO**  
**CAM FOLLOWERS**  
Eccentric Type Cam Followers With Cage/With Hexagon Hole



CFE-B

Outside diameter of eccentric collar mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d <sub>e</sub>
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
16	CFE 12-1 B						115	32	14	16

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N	
G	B <sub>3</sub>	B <sub>max</sub>	B <sub>1 max</sub>	B <sub>2</sub>	C <sub>1</sub>	G <sub>1</sub>	G <sub>1</sub>	H <sub>max</sub>	Eccentricity e						
M12×1.5	11.5	15.2	40.2	25	0.6	6	13.5	6	0,6	0,8	21	21,9	7 910	9 790	9 790

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060459466
Diámetro interior	16 mm
Diámetro exterior	32 mm
Espesor	14 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE