


## Seguidor de leva CFE6-IKO - CFE6-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe6-iko>

**IKO**  
**CAM FOLLOWERS**  
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)																																										
	Shield type		Sealed type		$\phi$	D	C	$d_2$																																							
9	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	20.5	16	11	9																																							
<table border="1"> <thead> <tr> <th colspan="10">Boundary dimensions mm</th> </tr> <tr> <th>G</th> <th>B<sub>3</sub></th> <th>B<sub>1</sub> max</th> <th>B<sub>2</sub> max</th> <th>B<sub>2</sub></th> <th>C<sub>1</sub></th> <th>G<sub>1</sub></th> <th>G<sub>1</sub> (1)</th> <th>Excentricity e</th> <th>Mounting dimension f</th> <th>Maximum tightening torque N·m</th> <th>Basic dynamic load rating C N</th> <th>Basic static load rating C<sub>0</sub> N</th> <th>Maximum allowable static load N</th> </tr> </thead> <tbody> <tr> <td>M 6×1</td> <td>7.5</td> <td>12.2</td> <td>28.2</td> <td>16</td> <td>0.6</td> <td>*4</td> <td>8.5</td> <td>0.3</td> <td>0.4</td> <td>11</td> <td>2.7</td> <td>3 660</td> <td>3 650</td> <td>1 950</td> </tr> </tbody> </table>									Boundary dimensions mm										G	B <sub>3</sub>	B <sub>1</sub> max	B <sub>2</sub> max	B <sub>2</sub>	C <sub>1</sub>	G <sub>1</sub>	G <sub>1</sub> (1)	Excentricity e	Mounting dimension f	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N	M 6×1	7.5	12.2	28.2	16	0.6	*4	8.5	0.3	0.4	11	2.7	3 660	3 650	1 950
Boundary dimensions mm																																															
G	B <sub>3</sub>	B <sub>1</sub> max	B <sub>2</sub> max	B <sub>2</sub>	C <sub>1</sub>	G <sub>1</sub>	G <sub>1</sub> (1)	Excentricity e	Mounting dimension f	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N																																		
M 6×1	7.5	12.2	28.2	16	0.6	*4	8.5	0.3	0.4	11	2.7	3 660	3 650	1 950																																	

### CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3616060459763
Diámetro interior	9 mm
Diámetro exterior	16 mm
Espesor	11 mm
Peso	20 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE