


Seguidor de leva CFE6-UU-IKO - CFE6-UU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe6-uu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		ϕ	D	C	d_2						
9	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 6 UU	20.5	16	11	9					
Boundary dimensions mm														
G	B ₃	B ₁ max	B ₂ max	B ₂	C ₁	G ₁	α	Mounting dimension f Min, mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N		
M 6×1	7.5	12.2	28.2	16	0.6	*4	8.5	0.3	0.4	11	2.7	3 660	3 650	1 950

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
N° Ean13	3616060459770
Diámetro interior	9 mm
Diámetro exterior	16 mm
Espesor	11 mm
Peso	20 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE