

## Seguidor de leva CFE24-1-IKO - CFE24-1-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe24-1-iko>

**IKO**  
**CAM FOLLOWERS**  
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**

| Outside diameter of eccentric roller mm | Identification number   |                             |                         |                             | Mass (Ref.) |    |    |                |
|-----------------------------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|----|----|----------------|
|                                         | Shield type             |                             | Sealed type             |                             | g           | D  | C  | d <sub>2</sub> |
| 33                                      | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | 1 220       | 72 | 29 | 33             |
| CFE 24-1                                |                         |                             |                         |                             |             |    |    |                |

  

| Boundary dimensions mm |                |       |                    |                |                |                |                |           |     | Essentiality | Mounting dimension f Min. mm | Maximum tightening torque N-m | Basic dynamic load rating C N | Basic static load rating C <sub>0</sub> N | Maximum allowable static load N |
|------------------------|----------------|-------|--------------------|----------------|----------------|----------------|----------------|-----------|-----|--------------|------------------------------|-------------------------------|-------------------------------|-------------------------------------------|---------------------------------|
| G                      | B <sub>3</sub> | B max | B <sub>1</sub> max | B <sub>2</sub> | C <sub>1</sub> | g <sub>1</sub> | G <sub>1</sub> | (1) r/min | e   |              |                              |                               |                               |                                           |                                 |
| M24×1.5                | 25.5           | 30.6  | 80.1               | 49.5           | 0.8            | 8              | 24             | 1         | 0.8 | 40           | 215                          | 30 500                        | 52 600                        | 52 000                                    |                                 |

### CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | IKO           |
| Nº Ean13          | 3616060460158 |
| Diámetro interior | 33 mm         |
| Diámetro exterior | 72 mm         |
| Espesor           | 29 mm         |
| Peso              | 1220 g        |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE