


Seguidor de leva CFE6-VB-IKO - CFE6-VB-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe6-vb-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



CFE6-VB

Outside diameter of eccentric collar mm	Identification number					Mass (Ref.)			
	Shield type		Sealed type			g	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
9	CFE 6 VB				21	16	11	9	

Boundary dimensions mm									
G	B ₃	B ₁ max	B ₂ max	C ₁	G ₁	H	f _{max}	f _{min}	Mounting dimension mm
M 6×1	7.5	12.2	28.2	16	0.6	—	8.5	3	0.3/0.4

Mounting dimension mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
11	2.7	6 980	8 500	1 950

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060460301
Diámetro interior	9 mm
Diámetro interior	0.354" inch
Diámetro exterior	16 mm
Diámetro exterior	0.63" inch
Espesor	11 mm
Espesor	0.433" inch
Peso	21 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE