


Seguidor de leva CFE24-VB-IKO - CFE24-VB-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe24-vb-iko>

IKO
CAM FOLLOWERS

Eccentric Type Cam Followers **Full Complement Type/With Hexagon Hole**



CFE-VB

Outside diameter of eccentric collar mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
33	CFE 24 VB						900	62	29	33

Boundary dimensions mm										
G	B ₃	B ₁ max	B ₂ max	B ₂	C ₁	G ₁	H	H _{max} (°)	f mm	Mounting dimension g
M24 X 1.5	25.5	30.6	80.1	49.5	0.8	8	24	12	1	0.8

Mounting dimension f mm	Maximum spring torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
40	215	46 600	92 000	52 000

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060460691
Diámetro interior	33 mm
Diámetro interior	1.299" inch
Diámetro exterior	62 mm
Diámetro exterior	2.441" inch
Espesor	29 mm
Espesor	1.142" inch
Peso	900 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE