


Seguidor de leva CFE30-1-VBUU-IKO - CFE30-1-VBUU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe30-1-vbuu-iko>

IKO
CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



CFE-VBUU

Outside diameter of eccentric collar mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
41						CFE 30-1 VBUU	2 190	85	35	41

Boundary dimensions mm															
G	B ₃	B ₁ max	B ₂ max	C ₁	G ₁	H	H _{max} (°)	Eccentricity g	Mounting dimension f mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N		
M30×1.5	32.5	37	100	63	1	8	30.5	17	1	1.5	49	438	67 700	144 000	85 900

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060460837
Diámetro interior	41 mm
Diámetro interior	1.614" inch
Diámetro exterior	85 mm
Diámetro exterior	3.346" inch
Espesor	35 mm
Espesor	1.378" inch
Peso	2190 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE