


Seguidor de leva CFE12-1-V-IKO - CFE12-1-V-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe12-1-v-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
16	CFE 12-1 V				117	32	14	16

Boundary dimensions mm														
G	B ₃	B _{max}	B ₂ max	B ₂	C ₁	g ₁	G ₁	r ₁ min	Excentricity E	Mounting dimension f Min. mm	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M12 × 1.5	11.5	15.2	40.2	25	0.6	6	13.5	0.6	0.8	21	21.9	13 500	19 700	13 200

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060461063
Diámetro interior	16 mm
Diámetro exterior	32 mm
Espesor	14 mm
Peso	117 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE