

Seguidor de leva CFE16-VR-IKO - CFE16-VR-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe16-vr-iko>

IKO
CAM FOLLOWERS

Eccentric Type Cam Followers **Full Complement Type/With Screwdriver Slot**

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d ₀
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
22	CFE 16	VR			193	35	18	22

Boundary dimensions mm										
G	B ₃	B _{max}	B _{1max}	B ₂	C ₁	g ₁	G ₁	r _{1min}	E	f
M16 x 1.5	15.5	19.6	52.1	32.5	0.8	6	17	0.6	0.8	26

Mounting dimension	Maximum operating torque	Basic dynamic load rating	Basic static load rating	Maximum allowable static load
f	C	C ₀	C ₀	
mm	N·m	N	N	N
26	58.5	20 700	37 600	23 200

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060461094
Diámetro interior	22 mm
Diámetro exterior	35 mm
Espesor	18 mm
Peso	193 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE