

## Seguidor de leva CFE16-VUUR-IKO - CFE16-VUUR-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe16-vuur-iko>

**IKO**  
**CAM FOLLOWERS**

Eccentric Type Cam Followers **Full Complement Type/With Screwdriver Slot**

| Outside diameter of eccentric outer ring<br>mm | Identification number   |                             |                         |                             | Mass (Ref.) |    |    |                |
|--|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|----|----|----------------|
|  | Shield type             |                             | Sealed type             |                             | g           | D  | C  | d <sub>e</sub> |
|  | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring |             |    |    |                |
| <b>22</b>                                      |                         |                             | <b>CFE 16</b>           | <b>VUUR</b>                 | 193         | 35 | 18 | 22             |

  

| Boundary dimensions mm |                |                  |                       |                |                |                |                |                       |                   |                                       |                                 |                                     |   |                                    |
|------------------------|----------------|------------------|-----------------------|----------------|----------------|----------------|----------------|-----------------------|-------------------|---------------------------------------|---------------------------------|-------------------------------------|---|------------------------------------|
| G                      | B <sub>3</sub> | B <sub>max</sub> | B <sub>1</sub><br>max | B <sub>2</sub> | C <sub>1</sub> | g <sub>1</sub> | G <sub>1</sub> | r <sub>1</sub><br>min | Eccentricity<br>E | Mounting dimension<br>f<br>Min.<br>mm | Maximum operating torque<br>N·m | Basic dynamic load rating<br>C<br>N | Basic static load rating<br>C <sub>0</sub><br>N | Maximum allowable static load<br>N |
| M16 x 1.5              | 15.5           | 19.6             | 52.1                  | 32.5           | 0.8            | 6              | 17             | 0.6                   | 0.8               | 26                                    | 58.5                            | 20 700                              | 37 600  | 23 200                             |

### CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | IKO           |
| Nº Ean13          | 3616060461117 |
| Diámetro interior | 22 mm         |
| Diámetro interior | 0.866" inch   |
| Diámetro exterior | 35 mm         |
| Diámetro exterior | 1.378" inch   |
| Espesor           | 18 mm         |
| Espesor           | 0.709" inch   |
| Peso              | 193 g         |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE