


Seguidor de leva CFE16-VUU-IKO - CFE16-VUU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe16-vuu-iko>

IKO
CAM FOLLOWERS

Eccentric Type Cam Followers **Full Complement Type/With Screwdriver Slot**



CFE16-VUU

Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		g	D	C	d _e						
22	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					193	35	18	22		
CFE 16 VUU														
Boundary dimensions mm														
G	B ₃	B _{max}	B ₁ max	B ₂	C ₁	g ₁	G ₁	r ₁ min	Excentricity E	Mounting dimension f Min. mm	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M16 x 1.5	15.5	19.6	52.1	32.5	0.8	6	17	0.6	0.8	26	58.5	20 700	37 600	23 200

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060461124
Diámetro interior	22 mm
Diámetro exterior	35 mm
Espesor	18 mm
Peso	193 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE