


Seguidor de leva CFE30-V-IKO - CFE30-V-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe30-v-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
41	CFE 30 V				2 030	80	35	41

Boundary dimensions mm														
G	B ₃	B _{max}	B ₂ _{max}	B ₂	C ₁	g ₁	G ₁	r ₁ _{min}	Eccentricity E	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M30 × 1.5	32.5	37	100	63	1	8	30.5	1	1.5	49	438	67 700	144 000	85 900

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060461315
Diámetro interior	41 mm
Diámetro exterior	80 mm
Espesor	35 mm
Peso	2030 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE