

Seguidor de leva CFE30-1-VUUR-IKO - CFE30-1-VUUR-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cfe30-1-vuur-iko>

IKO
CAM FOLLOWERS

Eccentric Type Cam Followers **Full Complement Type/With Screwdriver Slot**

CFE -- VUUR

Outside diameter of eccentric collar mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
41	CFE 30-1 VUUR				2 190	85	35	41

Boundary dimensions mm										
G	B ₃	B _{max}	B ₁ _{max}	B ₂	C ₁	g ₁	G ₁	r ₁ _{min} (°)	Excentricity E	Mounting dimension f Min. mm
M30 x 1.5	32.5	37	100	63	1	8	30.5	1	1.5	49
										Maximum tightening torque N·m
										438
										Basic dynamic load rating C N
										67 700
										Basic static load rating C ₀ N
										144 000
										Maximum allowable static load N
										85 900

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060461360
Diámetro interior	41 mm
Diámetro exterior	85 mm
Espesor	35 mm
Peso	2190 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE