


## Seguidor de leva CR12-BUUR-IKO - CR12-BUUR-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cr12-buur-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
9.525 ( $\frac{3}{8}$ )	CR 12 BUUR				35	19.050 ( $\frac{7}{8}$ )	12.700 ( $\frac{1}{2}$ )	9.525 ( $\frac{3}{8}$ )	F <sub>1</sub> -24	9.525 ( $\frac{3}{8}$ )	
Boundary dimensions mm/inch											
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	E <sub>1</sub>	E <sub>2</sub>	H	r	Bearing dimension f Mm/ mm(inch)	Maximum ignoring torque C N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N
14.2 0.56	22.25 ( $\frac{7}{8}$ )	6.350 ( $\frac{1}{4}$ )	0.794 ( $\frac{1}{16}$ )	4.762 ( $\frac{3}{8}$ )	2.381 ( $\frac{1}{8}$ )	4.762 ( $\frac{3}{8}$ )	0.794 ( $\frac{1}{16}$ )	13.494 ( $\frac{1}{2}$ )	10.8	4 420	5 110

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060462428
Diámetro interior	9.525 mm
Diámetro exterior	19.05 mm
Espesor	12.7 mm
Peso	35 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE