

Seguidor de leva CR18-UUR-IKO - CR18-UUR-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cr18-uur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
11.112 ($\frac{7}{16}$)			CR 18 / UUR		88	28.575 ($\frac{1}{2}$)	15.875 ($\frac{1}{2}$)	11.112 ($\frac{7}{16}$)	$\frac{1}{8}$ -20	12.700 ($\frac{1}{2}$)
Boundary dimensions mm[inch]										
B max	B ₂	B ₃	C ₁	S ₁	S ₂	r	Bearing dimension f Min. mm[inch]	Maximum tightening torque C N·m	Basic dynamic load rating C ₀ N	Basic static load rating C ₀ N
17.3 0.68	25.400 (1)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	3.175 ($\frac{1}{8}$)	1.588 ($\frac{1}{16}$)	19.050 ($\frac{3}{4}$)	17.4	9 190	11 600

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060462961
Diámetro interior	11.112 mm
Diámetro interior	7/16" inch
Diámetro exterior	28.575 mm
Diámetro exterior	1 1/8" inch
Espesor	15.875 mm
Espesor	5/8" inch
Peso	88 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE