


Seguidor de leva CR26-IKO - CR26-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cr26-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
15.875 (5/8)	CR 26				260	41.275 (1 5/8)	22.225 (7/8)	15.875 (5/8)	J ₁ -18	19.050 (3/4)
Boundary dimensions mm(inch)										
B max	B ₂	B ₃	C ₁	δ ₁	δ ₂	r	Bearing dimension f Min. mm(inch)	Maximum tightening torque C N·m	Basic dynamic load rating C ₀ N	Basic static load rating C ₀ N
23.8 (93)	38.100 (1 1/2)	9.525 (3/8)	0.794 (1/32)	4.702 (3/16)	3.969 (1/8)	1.588 (1/16)	26.199 (1 1/8)	55.7	10 800	24 300

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060463005
Diámetro interior	15.875 mm
Diámetro interior	5/8" inch
Diámetro exterior	41.275 mm
Diámetro exterior	1 5/8" inch
Espesor	22.225 mm
Espesor	7/8" inch
Peso	260 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE