


Seguidor de leva CR26-UUR-IKO - CR26-UUR-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cr26-uur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type							
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring						
15.875 ($\frac{5}{8}$)			CR 26 / UUR		260	41.275 ($1\frac{1}{2}$)	22.225 ($\frac{7}{8}$)	15.875 ($\frac{5}{8}$)	$\frac{1}{4}$ -18	19.050 ($\frac{3}{4}$)
Boundary dimensions mm(inch)										
B max	B ₂	B ₃	C ₁	S ₁	S ₂	r	Bearing dimension f Min. mm(inch)	Maximum tightening torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
23.8 (9.37)	38.100 ($1\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	0.794 ($\frac{1}{16}$)	4.702 ($\frac{3}{16}$)	3.969 ($\frac{1}{8}$)	1.588 ($\frac{1}{16}$)	26.199 ($1\frac{1}{8}$)	55.7	10 800	24 300

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060463012
Diámetro interior	15.875 mm
Diámetro exterior	41.275 mm
Espesor	22.225 mm
Peso	260 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE