

Seguidor de leva CR8-V-IKO - CR8-V-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cr8-v-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



| Stud dia. mm (inch) | Identification number | | | | Mass (Ref.) | | | | | |
|---------------------------|-----------------------|-----------------------------|--------------------------|-----------------------------|----------------|--------|-------|-------|----------|-------|
| | Shield type | | Shield type | | ϕ | D | C | d_1 | G | G_1 |
| | With cover | With cylindrical outer ring | With shielded outer ring | With cylindrical outer ring | | | | | UNF | |
| 4.826 | | CR 8 V | | | 9 | 12.700 | 8.731 | 4.826 | No.10-32 | 6.350 |

| Boundary dimensions mm(inch) | | | | | | | Mounting dimension f Min. mm(inch) | Maximum tightening torque N·m | Basic dynamic load rating C N | Basic static load rating C_0 N |
|------------------------------|------------|-------|--------------|--------------|-------|--------------|---|--|--|---|
| B_{max} | B_2 | B_3 | C_1 | g_1 | g_2 | r | | | | |
| 15.2(0.40) | 12.7(0.50) | - (-) | 0.794(0.031) | 1.175(0.046) | - (-) | 0.387(0.015) | 0.324(0.013) | 1.4 | 4 260 | 4 750 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | IKO |
| N° Ean13 | 3616060463098 |
| Diámetro interior | 4.826 mm |
| Diámetro exterior | 12.7 mm |
| Espesor | 8.731 mm |
| Peso | 9 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE