


## Seguidor de leva CR14-VBUU-IKO - CR14-VBUU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cr14-vbuu-iko>

IKO  
**CAM FOLLOWERS**  
Inch Series Cam Followers **With Cage/With Screwdriver Slot**



CR14-VBUU

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring							
9.525 ( $\frac{3}{8}$ )				CR 14 VBUU	47	22.225 ( $\frac{7}{8}$ )	12.700 ( $\frac{1}{2}$ )	9.525 ( $\frac{3}{8}$ )	$\frac{1}{8}$ -24	9.525 ( $\frac{3}{8}$ )	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N		
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>					H	r
14.2 0.56	22.225 ( $\frac{7}{8}$ )	6.350 ( $\frac{1}{4}$ )	0.794 ( $\frac{1}{16}$ )	4.762 ( $\frac{3}{16}$ )	2.381 ( $\frac{3}{32}$ )	4.762 ( $\frac{3}{16}$ )	0.794 ( $\frac{1}{16}$ )	15.081 ( $\frac{5}{8}$ )	10.8	8 710	12 300

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060463531
Diámetro interior	9.525 mm
Diámetro exterior	22.225 mm
Espesor	12.7 mm
Peso	47 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE