


## Seguidor de leva CR16-VBUU-IKO - CR16-VBUU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cr16-vbuu-iko>

IKO  
**CAM FOLLOWERS**  
Inch Series Cam Followers **With Cage/With Screwdriver Slot**



CR16-VBUU

| Stud dia.<br>mm<br>(inch)    | Identification number    |                             |                          |                             | Mass<br>(Ref.)          |                          |                          |   |                                  |                                |  |
|------------------------------|--------------------------|-----------------------------|--------------------------|-----------------------------|-------------------------|--------------------------|--------------------------|---|----------------------------------|--------------------------------|--|
|                              | Shield type              |                             | Sleeve type              |                             | g                       | D                        | C                        | d <sub>1</sub>                              | G                                | G <sub>1</sub>                 |  |
|                              | With cover               | With cylindrical outer ring | With groove outer ring   | With cylindrical outer ring |                         |                          |                          |   |                                  |                                |  |
| 11.112<br>( $\frac{7}{16}$ ) |                          |                             |                          | CR 16 VBUU                  | 74                      | 25.400 ( $\frac{1}{1}$ ) | 15.875 ( $\frac{5}{8}$ ) | 11.112 ( $\frac{7}{16}$ )                   | $\frac{3}{8}$ -20                | 12.700 ( $\frac{1}{2}$ )       |  |
| Boundary dimensions mm(inch) |                          |                             |                          |                             |                         |                          |                          |   |                                  |                                |  |
| B <sub>max</sub>             | B <sub>2</sub>           | B <sub>3</sub>              | C <sub>1</sub>           | g <sub>1</sub>              | g <sub>2</sub>          | H                        | r                        | Mounting dimension<br>f<br>Min.<br>mm(inch) | Maximum tightening torque<br>N·m | Basic dynamic load rating<br>C | Basic static load rating<br>C <sub>0</sub> |
| 17.3 (0.68)                  | 25.400 ( $\frac{1}{1}$ ) | 6.350 ( $\frac{1}{4}$ )     | 0.794 ( $\frac{1}{32}$ ) | 4.782 ( $\frac{3}{16}$ )    | 3.175 ( $\frac{1}{8}$ ) | 6.350 ( $\frac{1}{4}$ )  | 1.191 ( $\frac{1}{8}$ )  | 17.859 ( $\frac{3}{4}$ )                    | 17.4                             | 13 100                         | 22 700                                     |

## CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | IKO           |
| N° Ean13          | 3616060463616 |
| Diámetro interior | 11.112 mm     |
| Diámetro interior | 7/16" inch    |
| Diámetro exterior | 25.4 mm       |
| Diámetro exterior | 1" inch       |
| Espesor           | 15.875 mm     |
| Espesor           | 5/8" inch     |
| Peso              | 74 g          |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE