


Seguidor de leva CR24-VB-IKO - CR24-VB-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cr24-vb-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers **With Cage/With Screwdriver Slot**



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring							
15.875 ($\frac{5}{8}$)		CR 24 VB			230	38.100 (1 $\frac{1}{2}$)	22.225 (1 $\frac{1}{2}$)	15.875 (1 $\frac{1}{2}$)	1-18	19.050 (1 $\frac{1}{2}$)	
Boundary dimensions mm(inch)											
B max	B ₂	B ₃	C ₁	g ₁	g ₂	H	r	Mounting dimension f Min. mm(inch)	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N
23.8 (0.93)	38.100 (1 $\frac{1}{2}$)	9.525 (1 $\frac{1}{2}$)	0.794 ($\frac{1}{4}$)	4.762 ($\frac{1}{4}$)	3.969 ($\frac{1}{4}$)	7.938 ($\frac{1}{2}$)	1.588 ($\frac{1}{4}$)	26.195 (1 $\frac{1}{2}$)	55.7	29 200	40 100

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060463913
Diámetro interior	15.875 mm
Diámetro exterior	38.1 mm
Espesor	22.225 mm
Peso	230 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE